

SF-300 LIFT

This medium sized mini lift is capable of lifting up to 300 kg and are designed for prolonged daily use in the Food and Beverage Industry. The twin lifting column design delivers added stability, making it the perfect choice for applications requiring high reach and/or loads placed far in front of the lifting columns.

GMP lift
with added
stability and long
battery capacity

**Ready
for the future
with eMobility?**
Can be adapted for
self-propelled driving
with **Power Drive**

DESIGNED FOR SAFETY
BUILT TO LAST
OHS COMPLIANT + MADE IN DENMARK

Lift Construction

- Full stainless steel (AISI 304); glass bead blasted surface; 1.6 Ra
- Dust and water protection class IP65, hygienic - easy to clean
- Dimensions customizable to your needs

Safety

- Self-locking gear system (worm gear): in the event of an electrical failure, the mechanical system automatically brings the lifter to an immediate stop
- Safety slip clutch (one-way safety clutch): prevents the lifter from lifting itself and tipping backwards during downward movement

Handling

- Electric lifting process controlled via a toggle switch; lifting speed can be adjusted via the adjustment knob
- Two lifting speeds: Normal (approx. 130 mm/s) and reduced speed, pre-set to e.g. 30%. The reduced speed can be adjusted in the control box on the lift

Lightweight and compact dimensions well suited for use in spatially demanding work areas

- Robust remote control (full metal body; high quality PU spiral cable) allows easy one-hand operation
- Ergonomic handle that allows the user different gripping positions

Power Supply

- Battery-operated
- Can be permanently connected to power (Power supply: 110-230 V AC)
- Intelligent internal battery charger - 24V 3.5A. Ensures long battery life through on-demand charging. You are always informed about the battery charge state by the integrated LED display

Maintenance

- Low maintenance AT-10 timing belt
- Very durable Solid-State PLC
- Wear-resistant parts (Wheels and maintenance-free standard batteries without memory effect)



Technical Specifications

✓ Adaptable

Standard & Customised	Low	Medium	High	Customised
Totalhøjde mm	1.500	1.974	2.350	1.310-3.500
Slaglængde mm	895	1.380	1.760	696-2.896

Max. load without tool	300 kg	
IP Safety	65	
Min. - Max. lifting height	Depending on the tool	✓
Surface	AISI 304 Glass Bead Blasted	
Lifting speed	130 mm/s	✓
Control Unit	Solid State PLC	
User Control System	Remote control with E-stop for manipulators	
Overload Protection	Current monitor with cut-off	
Battery Charger	Built in - 24V 3.5A	
Battery Capacity	24 V - 18 Ah	
Power Supply	230 V, 110 V	
Time to charge	Max. 6 hrs.	
Number of lifts 300 kg/1m	130 per full charge	
Footprint (LxW)	1252x780 mm	
Rear Wheels	ø125 mm - with break	✓
Front Wheels	ø80 mm	✓
Length of legs*	700 mm	✓
Height of legs*	80 mm	✓
Width of legs (outside)*	560 mm	✓
Width of legs (inside)*	440 mm	✓

* Standard dimensions; customization of dimensions may be necessary depending on the mounted lifting tool.

Tool Modules

AF	Adjustable fork for handling different box sizes	ERU-MLC	Manual linear clamping unit for barrels with electric 180° rotation in both directions
AM	Adjustable mandrel for lifting rolls with a horizontal core direction	ERU-MP	Barrel gripper with protective base plate for pressure-sensitive barrels/drums. Can rotate 90° in each direction
BT	Electric box tipper	F	Fork for lifting a box of a given size
DG	Edge gripper with support for pressure-sensitive barrels	FN	Fork with notch for lifting rolls through the core
DL	Neck gripper for pressure-sensitive barrels/rolls	FTS	Fork with self-locking edge gripper, ideal for metal boxes
DM	Double mandrel for lifting rolls without passing through the core	M	Mandrel for lifting rolls with a horizontal core direction
EC	Electric scissor gripper with soft rubber for barrels/boxes of 300-600 mm diameter	MC	Manual Clamp
ELC	Electric Linear Clamping Unit for Barrels/Rolls	MLC	Manual Linear Clamp
ELC-ETU	Electric Linear Clamping Unit for Barrels/Rolls with electric 180° tipping unit	MLC-MTU	Manual Linear Clamp with Manual Tipping Unit
ELC-MTU	Electric Linear Clamping Unit for Barrels with manuel 180° tipping unit	MP/R/E	Metal Platform without (MP)/with edge Rollers (MPR), with Edges (MPE)
ERM	Electric roll manipulator	MRM	Manual Roll Manipulator
ERU-DF	Electric double fork with electric 180° rotation in both directions	MRU-MLC	Manual Rotation Unit with Manual Linear Clamp
ERU-DM	Electric double pin gripper with electric 180° rotation in both directions	NP	Nylon Platform
ERU-EC	Electric 360° rotation unit with electric scissor gripper with soft rubber for items between 300-600 mm diameter	RM	Mandrel with Rollers and brake for lifting rolls with a horizontally remaining core
ERU-F	Electric 360° rotation unit with fork gripper for alternative box dimensions	VB	V-block for rolling/tipping rolls. Can be manually rotated so the roll can be lifted via the core

DENMARK 2LIFT ApS
+45 61 70 16 15 Nordrupvej 65
GERMANY DK-4200 Slagelse
+49 711 9688 9788 info@2lift.com

